

DOUBLE WALL HEAT SHRINK TUBING WITH 3:1 ADHESIVE



Technical description

Color: Black Material: cross-linked polyolefin with co-extrusion-applied adhesive Shrinkage factor: 3:1 Self-extinguishing agent: UL224 VW-1 Flame retardant Excellent impermeabilization and insulation UV resistant Operating temperature: -55 °C +125 °C Minimum shrinkage temperature: +70 °C Minimum total shrinkage temperature: +110 °C Longitudinal variation 0 ± 10% max. All dimensions are in mm



Code	As supplied: inside Ø	After recovery: inside diameter (max.)	After recovery: wall thick.	Reel / Meter
14826RA01	3,0	1,0	1,00	150,0
14827RA01	4,8	1,5	1,00	75,0
14828RA01	6,0	2,0	1,00	75,0
14829RA01	9,0	3,0	1,35	50,0

Code	As supplied: inside Ø	After recovery: inside diameter (max.)	After recovery: wall thick.	Reel / Meter
14830RA01	12,0	4,0	1,65	30,0
14831RA01	19,0	6,4	2,10	30,0
14832RA01	24,0	8,0	2,35	30,0
14833RA01	30,0	10,0	2,40	30,0
14834RA01	40,0	13,0	2,40	30,0