

MEDIUM WALL THICKNESS HEAT SHRINKABLE SHEATHING



Technical description

Colour: Black

Medium-wall tubing without hot melt adhesive

Material: Crosslinked Polyolefin

Shrink ratio: 3:1

Good environmental protection

Ideal for low voltage applications

UV resistant

Operating temperature: -55 °C +110 °C

Minimum full recovery temperature: +120 °C

Longitudinal change $0 \pm 10\%$ massimo

All dimensions are in mm



Code	As supplied: inside Ø	After recovery: inside diameter (max.)	After recovery: wall thick.	Bars length mt
14348RA01	12,0	3,0	1,8	1,22
14349RA01	16,0	5,0	2,10	1,22
14350RA01	22,0	6,0	2,40	1,22
14351RA01	33,0	8,0	2,6	1,22
14352RA01	40,0	12,0	2,6	1,22
14353RA01	55,0	16,0	2,7	1,22
14354RA01	65,0	19,0	2,9	1,22
14355RA01	75,0	22,0	3,0	1,22
14356RA01	95,0	25,0	3,6	1,22
14357RA01	115,0	34,0	3,5	1,22
14358RA01	140,0	42,0	3,3	1,22
14359RA01	160,0	50,0	3,3	1,22
14360RA01	180,0	58,0	3,3	1,22
14361RA01	265,0	75,0	3,8	1,22
14362RA01	300,0	75,0	3,8	1,22
13188RA01	350,0	100,0	4,3	1,22