

SEMI-OPEN RIGID GROMMETS WITH MEMBRANE



Technical description

Material: PA 6.6

Color: black

Self-extinguishing: V2 (UL 94)

Working temperature:




1071xAA01: -35°C ~ +85°C

1525xAA01: -18°C ~ +105°C

1846XAA01: -18°C ~ +105°C

C= maximum inner diameter

All dimensions are in mm.



Code	A	B	C	Mounting hole	Thickness	MOQ-Pcs
10710AA01	15,3	9,8	10,3	Ø 12,7	0,8 - 3,3	1.000
10711AA01	18,8	10,3	13,8	Ø 15,9	0,8 - 3,3	1.000
10712AA01	25,5	10,3	18,5	Ø 22,2	0,8 - 3,3	250

Code	A	B	C	Mounting hole	Thickness	MOQ-Pcs
10713AA01	31,5	10,3	25,5	Ø 27,8	0,8 - 3,3	200
10714AA01	38,7	10,3	29,3	Ø 31,8	0,8 - 3,3	200
10715AA01	39,2	10,3	31,2	Ø 34,9	0,8 - 3,3	200
10716AA01	42,6	10,7	32,6	Ø 38,1	0,8 - 3,3	200
15250AA01	14,2	9,8	Ø 12,7	3,2	1.000	
15251AA01	17,5	10,3	Ø 15,9	3,2	1.000	
15252AA01	20,3	10,3	Ø 19,1	3,2	1.000	
15253AA01	23,4	10,3	Ø 22,2	3,2	1.000	
15254AA01	26,7	10,3	Ø 25,4	3,2	1.000	
15255AA01	29,5	10,3	Ø 27,8	3,2	1.000	
15256AA01	36,6	10,3	23,8	Ø 31,8	3,2	1.000
15257AA01	36,6	10,3	25,4	Ø 34,9	3,2	1.000
15258AA01	39,6	10,7	26,9	Ø 38,1	3,2	1.000
18461AA01	53,9	10,7	Ø 50,8	3,2	1.000	
18462AA01	66,0	18,3	Ø 63,5	6,4	450	