

RIVET RELEASABLE



Technical description

Material: PA 6


Colour: Black

special request: Colour White

UL Flammability: V2 (UL 94)

Operating temperature: -35°C ~ +85°C

All dimensions are in mm.



Code	A	B	C	Mounting hole	Thickness	MOQ-Pcs
9733AA01	6,4	1,0	3,5	Ø 3,1	1,0 - 2,0	1.000
9741AA01	6,4	1,0	3,5	Ø 3,6	1,0 - 2,0	1.000
9734AA01	6,4	1,0	4,5	Ø 3,1	2,0 - 3,0	1.000
9742AA01	6,4	1,0	4,5	Ø 3,6	2,0 - 3,0	1.000
9735AA01	6,4	1,0	5,5	Ø 3,1	3,0 - 4,0	1.000
9743AA01	6,0	1,0	5,5	Ø 3,6	3,0 - 4,0	1.000
9744AA01	6,0	1,0	6,0	Ø 3,6	3,5 - 4,5	1.000
9736AA01	6,0	1,0	6,5	Ø 3,1	4,0 - 5,0	1.000
9745AA01	6,0	1,0	7,0	Ø 3,6	4,5 - 5,5	1.000

Code	A	B	C	Mounting hole	Thickness	MOQ-Pcs
9737AA01	6,0	1,0	7,5	Ø 3,1	5,0 - 6,0	1.000
9738AA01	6,0	1,0	8,0	Ø 3,1	5,0 - 6,5	1.000
9746AA01	6,0	1,0	8,0	Ø 3,6	5,5 - 6,5	1.000
9739AA01	6,4	1,0	9,0	Ø 3,1	6,5 - 7,5	1.000
9740AA01	6,4	1,0	10,0	Ø 3,1	7,5 - 8,5	1.000