



THREADED SNAP LOCK SPACERS – HOLE Ø 3,0



Technical description

Material: PA 6.6 Colour: Natural Flammability: V2 (UL94) Working temperature: -35°C ~ +85°C All dimensions are in mm



Code	A	B	C	D	Mounting hole	Thickness	MOQ-Pcs
12652AA0005.0	5,0	3,0	5,5	M3 x 0,5P	Ø 3,0	1,6	2.000
12652AA0006.0	6,0	4,0	5,5	M3 x 0,5P	Ø 3,0	1,6	2.000
12652AA0007.0	7,0	4,0	5,5	M3 x 0,5P	Ø 3,0	1,6	2.000
12652AA0008.0	8,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	2.000

Code	A	B	C	D	Mounting hole	Thickness	MOQ-Pcs
12652AA0009.0	9,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	2.000
12652AA0010.0	10,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	2.000
12652AA0011.0	11,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	1.000
12652AA0012.0	12,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	1.000
12652AA0013.0	13,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	1.000
12652AA0014.0	14,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	1.000
12652AA0015.0	15,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	1.000
12652AA0016.0	16,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	1.000
12652AA0017.0	17,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	1.000
12652AA0018.0	18,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	1.000
12652AA0019.0	19,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	1.000
12652AA0020.0	20,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	1.000
12652AA0022.0	22,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	1.000
12652AA0023.5	23,5	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	1.000
12652AA0026.0	26,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	1.000
12652AA0027.0	27,0	6,0	5,5	M3 x 0,5P	Ø 3,0	1,6	1.000