




DIM.	TOL.
5mm DOWN	±0.2
5~20mm	±0.3
20~40mm	±0.4
40~60mm	±0.5
60~100mm	±0.8
100mm UP	±1.0


REVISIONS			
REV	DESCRIPTION	DATE	BY



TYPE 2




TYPE 1



P/N	HOLE	A	B	TYPE
18424NA00	Ø 4,7	6,4	5,9	1
18425NA00	Ø 6,4	7,9	7,9	1
18426NA00	Ø 7,9	9,5	7,9	1
18427NA00	Ø 9,5	11,9	10,3	2
18428NA00	Ø 11,1	13,5	10,3	2
18429NA00	Ø 12,7	14,3	10,3	2
5777NA00	Ø 15,9	18,6	10,3	2
18430NA00	Ø 19,3	21,8	10,3	2
18431NA00	Ø 22,2	24,2	11,5	2
18432NA00	Ø 25,4	28,6	11,5	2
18433NA00	Ø 27,8 -28,6	30,9	11,5	2
18434NA00	Ø 34,9	38,1	11,5	2
18435NA00	Ø 38,1	41,2	11,5	2
18436NA00	Ø 44,4	48,3	11,5	2
18437NA00	Ø 50,8	54,8	11,5	2

NOTES:

SINGLE LOCKING STEPS FOR PANEL THICKNESS UP TO (1,6 MM)
MULTIPLE LOCKING STEPS FOR PANEL THICKNESS UP TO (3,2 MM)
WORKING TEMPERATURES -40°C...+115°C
AVAILABLE IN A VARIETY OF TINTS ON SPECIAL REQUEST

		TITLE WINDOW "VIEW PORT" PLUGS	
		MATERIAL PC V2(UL94)	DATE 11/07/2023
PART NUMBER SEE TABLE		DRAWN A.C.	
DRAWING NUMBER 23.07.11.XXXX.0.E		CHECK	
SIZE A4	SCALE NTS	COLOR CLEAR	APPROVED
UNIT mm.	REV A	UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE	